

544859A LAWNAIRE (3-POINT HITCH 36")

> 544860A LAWNAIRE (TOW BEHIND)

S MANUA

544876A LAWNAIRE (3-POINT HITCH 48")



CALIFORNIA Proposition 65 Warning

Diesel engine exhaust and some of its constituents are known to the State of California to cause cancer, birth defects and other reproductive harm.

A WARNING

The engine exhaust from this product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Californie Proposition 65 Avertissement

Les échappements des moteurs diesel et certains de leurs composés sont reconnus par l'Etat de Californie pour être cancérigènes, provoquer des défauts congénitaux et d'autres dangers en matière de reproduction.

A AVERTISSEMENT

L'émission du moteur de ce matériel contient des produits chimiques que l'Etat de Californie considère être cancérigènes, provoquer des défauts congénitaux et d'autres dangers en matière de reproduction.

California Advertencia de la Proposicion 65

El estado de California hace saber que los gases de escape de los motores diesel y algunos de sus componentes producen cáncer, defectos de nacimiento y otros daños en el proceso de reproducción humana.

A ADVERTENCIA

El estado de California hace saber que los gases de escape de este producto contienen productos quÍmicos que producen cáncer, defectos de nacimiento y otros daños en el proceso de reproducción humana.

CALIFORNIA Proposition 65 Warning

Battery posts, terminals, wiring insulation, and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

WASH HANDS AFTER HANDLING.

IMPORTANT MESSAGE

Thank you for purchasing this Ryan product. You have purchased a world class product, one of the best designed and built anywhere.

This machine comes with a Technical Manual containing safety, operation, parts and service information. The useful life and good service you receive from this machine depends to a large extent on how well you read and understand this manual. Treat your machine properly, lubricate and adjust it as instructed, and it will give you many years of reliable service.

Your safe use of this Ryan product is one of our prime design objectives. Many safety features are built in, but we also rely on your good sense and care to achieve accident-free operation. For best protection, study the manual thoroughly. Learn the proper operation of all controls. Observe all safety precautions. Follow all instructions and warnings completely. Do not remove or defeat any safety features. Make sure those who operate this machine are as well informed and careful in its use as you are.

See a Ryan dealer for any service or parts needed. Ryan service ensures that you continue to receive the best results possible from Ryan's products. You can trust Ryan replacement parts because they are manufactured with the same high precision and quality as the original parts.

Ryan designs and builds its equipment to serve many years in a safe and productive manner. For longest life, use this machine only as directed in the manual, keep it in good repair and follow safety warnings and instructions. You'll always be glad you did.

Schiller Grounds Care, Inc.
One Bob Cat Lane
Johnson Creek, WI 53038-0469

TABLE OF CONTENTS SAFETY	FIGURES	PAGE 2
SET-UP		
OPERATION		
SERVICE		
SPECIFICATIONS		13
ACCESSORIES		14
PARTS SECTION		15
HYDRAULIC LIFT ACCESSORY	FIGURE 1	16, 17
MANUAL LIFT ACCESSORY	FIGURE 2	18, 19
MODEL NO. 544859A	FIGURE 3	20, 21
MODEL NO. 544876A		
MODEL NO. 544860A	FIGURE 5	24, 25

6-2007

NOTICE !!!

Unauthorized modifications may present **extreme** safety hazards to operators and bystanders and could also result in product damage.

Schiller Grounds Care, Inc. strongly warns against, rejects and disclaims any modifications, add-on accessories or product alterations that are not designed, developed, tested and approved by Schiller Grounds Care, Inc.'s Engineering Department. Any Schiller Grounds Care, Inc. product that is altered, modified or changed in any manner not specifically authorized after original manufacture—including the addition of "after-market" accessories or component parts not specifically approved by Schiller Grounds Care, Inc.—will result in the Schiller Grounds Care, Inc. Warranty being voided.

Any and all liability for personal injury and/or property damage caused by any unauthorized modifications, add-on accessories or products not approved by Schiller Grounds Care, Inc. will be considered the responsibility of the individual(s) or company designing and/or making such changes. Schiller Grounds Care, Inc. will vigorously pursue full indemnification and costs from any party responsible for such unauthorized post-manufacture modifications and/or accessories should personal injury and/or property damage result.



This symbol means:
ATTENTION!
BECOME ALERT!

Your safety and the safety of others is involved.

Signal word definitions:

The signal words below are used to identify levels of hazard seriousness. These words appear in this manual and on the safety labels attached to Schiller Grounds Care, Inc. machines. For your safety and the safety of others, read and follow the information given with these signal words and/or the symbol shown above.

A DANGER

DANGER indicates an imminently hazardous situation which, if not avoided, **WILL** result in death or serious injury.

AWARNING

WARNING indicates a potentially hazardous situation which, if not avoided, **COULD** result in death or serious injury.

ACAUTION

CAUTION indicates a potentially hazardous situation which, if not avoided, **MAY** result in minor or moderate injury. It may also be used to alert against unsafe practices or property damage.

CAUTION

CAUTION used without the safety alert symbol indicates a potentially hazardous situation which, if not avoided, **MAY** result in property damage.

Schiller Grounds Care, Inc.

SERIAL NUMBER

Une Bobcat Lane Johnson Creek, WI 53038 U.S.A Phone: 920-699-2000 Fax: 920-699-3683

MODEL NUMBER

MODEL NUMBER: This number appears on sales literature, technical manuals and price lists.

SERIAL NUMBER: This number appears only on your mower. It contains the model number followed consecutively by the serial number. Use this number when ordering parts or seeking warranty information.

SET-UP

MODEL 544859A, 3-POINT HITCH 36" MODEL 544876A, 3-POINT HITCH 48"

A WARNING

Banding is under tension and may snap back when cut. Wear eye protection and stay clear when cutting the band.

Use caution when installing the knives and tines. These items are sharp and should be handled with care.

Use an appropriate jackstand to support the aerator any time it is serviced or repaired.

- 1. Remove and discard banding holding the aerator to the pallet.
- 2. Attach tractor to aerator and lift off pallet. For category 1 hitches, use the bushing (Part No. 829987) and the hitch pins.
- Place jackstands at each end of tine wheel axles and lower aerator onto stands. Aerator wheels need to be approximately 5 to 6 inches (127 to 152 mm) above the ground.
- 4. With tractor engine off, install the appropriate tools for your needs. Figure 1 shows coring tines mounted to the aerating wheels (8 tines per wheel). When using coring tines, the nipple on the inside of the tine clamp (Part No. 515198) must be placed into the hole on the sides of the tine. Refer to Parts List, Pages 21 and 23 for knife blade installation.

NOTE: To assure equal tine spacing, note the position of the tines in Figure 1. The middle wheels have the tines mounted on the inner side, the outside wheels have the tines mounted on the outer side. See Accessories (Page 14) for optional attachments.

 Lubricate aerating wheels with lithium based lubricant until lubricant can be seen at wheel bushings. Check aerating wheels for free rotation.




FIGURE 1
Tine Spacing



SET-UP

MODEL 544860A, TOW BEHIND

A WARNING

Banding is under tension and may snap back when cut. Wear eye protection and stay clear when cutting the band.

DO NOT use tractor hydraulics to hold up aerator for servicing. Hydraulic lines may rupture causing the unit to fall suddenly.

Use caution when installing the knives and tines. These items are sharp and should be handled with care.

- 1. Remove and discard banding holding aerator to pallet.
- 2. Locate and mark the center on the front side of the frame (Part No. 4163369.7). Mark the center of the hitch assembly (Part No. 4163370.2 in a location which can be seen when mounting it to the frame.
- 3. Using the center marks for alignment, mount the hitch assembly and clamping plate (Part No. 547741) to the frame. The hitch assembly will mount on the bottom side of the frame for small tractors, and on the top side of the frame for larger tractors.

NOTE: Install the manual lift accessory or the hydraulic lift accessory to the aerator before installing the tines or knife blades. An electric lift kit is also available (Part No. 4131949) which contains set-up instructions When used on a Bobcat or Bunton ZT200 mower, Hitch Kit (Part No. 970315) is also available to provide a hook-up point on the mower. Refer to the following installation instructions for the proper application of the hydraulic or manual lift accessory.

If the hydraulic lift accessory is used, secure the hitch and clamping plate using (3) 3/8-16 X 2-1/2" screws, lockwashers and nuts. Mount the hose support (Part No. 521905) onto the right front hole of the clamping plate. Secure, using a 3/8-16 X 3" screw, large flatwasher, lockwasher and nut. (The hardware for each accessory is included in the appropriate accessory kit).

If the manual lift accessory is used, secure the hitch and clamping plate to the frame with (4) 3/8-16 X 2-1/2" screws, lockwashers and nuts.

4. Attach tractor to the aerator and carefully pull aerator off the pallet. Stop tractor engine.

HYDRAULIC LIFT ACCESSORY PART NO. 545711

AWARNING

Escaping hydraulic oil under pressure can have sufficient force to penetrate the skin, causing serious injury.

If a leak is suspected, use a piece of cardboard or wood, not your hands, to check for leaks.

If injured by escaping fluid, see a doctor at once. Serious infection or reaction can develop if proper medical treatment is not administered immediately.

Do not use a unit with a leaking hydraulic system. See your authorized Ryan dealer for necessary repairs.

NOTE: This lift accessory is designed to be used with a hydraulic system providing 700 p.s.i. (4,824kPa) or 1500 p.s.i. (10,341kPa) working pressure. It may work on systems providing lower pressures, but will raise the aerator much slower.

AWARNING

Properly support the aerator, using jackstands, for removal of the right side transport wheel and leg assembly. For safe removal, the wheel and leg need to be at least 2 inches (50mm) above the ground and move freely in order to remove it from the axle shaft.

- 1. Remove the spirol pin, and the wheel and leg assembly from the right side of the axle shaft and retain for later use.
- 2. Install the cylinder mounting brackets (Part No. 522090) onto the right wheel leg assembly, using (4) 7/16-14 X 1" screws, lockwashers and nuts. See Figure 2, Page 6.
- 3. Install the woodruff key (Part No. 64164-35) into the keyway on the axle shaft, and slide the wheel and leg assembly back onto the axle. Secure with the spirol pin removed in Step 1.
- 4. Remove the (4) 7/16-14 X 1-3/4" screws securing the right frame arm (Part No. 521883) and cover to the frame (Part No. 545645). Retain hardware for later use.
- 5. Mount the cylinder pivot bracket (Part No. 545649) onto the frame arm using the original hardware. See Parts List, Page 17.
- 6. Install the hydraulic cylinder (Part No. 545787) in the appropriate holes on the cylinder pivot bracket and the wheel leg assembly, or the cylinder pivot bracket and the cylinder mounting brackets. See Figures 2 and 3, Page 6.

NOTE: The operator is responsible for acquiring the proper hoses and/or fittings that attach the hydraulic cylinder to the tractor directly to the cylinder, or the operator may install hydraulic fittings onto the cylinder.

For proper connection to the cylinder, use hoses or fittings with a 3/8-18 NPT. Fittings can be obtained from any local tractor dealer, or can be ordered through your Ryan dealer. See Parts List on Page 17 for appropriate fittings.

7. Install hydraulic hoses (not included with set) from tractor to cylinder, passing through the hose support. Raise and lower aerator to make sure hydraulic oil is circulated through entire system. Check for any loose or leaking connections and tighten or replace as necessary. Fill tractor hydraulic reservoir if necessary.




FIGURE 2 (For Tractors With 700 p.s.i. Hydraulics) 1. Cylinder Mounting Bracket

- 2. Wheel and Leg Assembly
- 3. Front Hole Position on Pivot Bracket

NOTE: For tractors with 700 p.s.i. (4,824 kPa), install the hydraulic cylinder using the front holes in the cylinder pivot bracket, and the holes of the cylinder mounting brackets. Figure 2.

For tractors with 1500 p.s.i. (10,341 kPa), install the hydraulic cylinder using the rear holes in the pivot mounting bracket, and the holes in the wheel and leg assembly. Figure 3.




FIGURE 3 (For Tractors With 1500 p.s.i. Hydraulics) 1. Rear Hole Position on Pivot Bracket

2. Wheel and Leg Assembly

MANUAL LIFT ACCESSORY PART NO. 545654 (For Tow Behind Lawnaire Model 544860A)

- 1. Remove the (2) 3/8-16 X 1-1/2" screws, securing the rear part of the cover to frame arm, on right side of aerator. Retain hardware for later use.
- 2. Install right stop assembly (Part No. 545675) to unit as shown in Illustration on Page 18. Secure stop with the original hardware.
- 3. Using the same procedure, install the left side stop (Part No. 645655).
- 4. Place the spring (Part No. 521880) between the uprights on the wheel leg. Insert the lock pin into the holes, passing lock pin through both leg uprights.
- 5. Pull the spring back and insert a cotter pin (Part No. 307976) through the hole in the lock pin. The cotter pin will be positioned between the spring and the leg upright. Repeat procedure on other side of unit.
- 6. To raise aerator, insert the lifting handle (Part No. 521892) into the tube on the wheel leg. Raise handle lowering wheel leg into a vertical position. Lock the locking pin into the hole on the stop bracket. Repeat on other side of unit.
- 7. To lower aerator, insert the lifting handle into the tube on the wheel leg. Push handle forward to relieve pressure on the locking pin. Pull pin out and raise the wheel, lowering the aerator. Repeat on opposite side of unit.
- 8. Replace lifting handle in tongue for storage. Insert pin (Part No. 521918) to secure lifting handle.

MODEL 544859A, 3-POINT HITCH 36" MODEL 544876A, 3-POINT HITCH 48"

AWARNING

Before operating the aerator, check area to be aerated, and remove any objects which may present a safety hazard or damage the aerator (rocks, cans, etc.)

To prevent injury, do not operate aerator without cover in place. Do not make adjustments or perform any maintenance while tractor engine is running.

Do not leave tractor unattended without stopping the engine and lowering the aerator.

NOTE: Failure to lubricate aerating wheels can cause damage to axle, bushings and wheels.

Never cross hard objects or surfaces (sidewalks, driveways, stepping stones, etc.) with tines down.

Do not back up when tines are in the ground or damage to the tines and clamps may occur.

For maximum performance, a double set of tines may be mounted onto the aerating wheels. A longer screw is required for this application. To obtain this screw, order Part No. 311213.

- 1. Position the tractor and aerator where you wish to begin aerating.
- 2. With tractor in motion, lower aerator and begin aerating.
- 3. After completion of job, clean and service the aerator according to the following service instructions.

TRANSPORT OF TOW BEHIND LAWNAIRE MODEL 544860A

1. With transport wheels lowered and locked into place, tow the aerator to and from job sites with aerator properly hitched to tractor drawbar. Maximum towing speed should not exceed 10 MPH (16 km/h).

AERATING LAWNAIRE MODEL 544860A

AWARNING

This unit is not designed nor meant to be towed at speeds in excess of 10 MPH (16 Km/h).

Towing at excessive speeds will cause damage to frame and/or wheels. This type of damage will not be repaired under the terms of the warranty.

Before operating the aerator, check area to be aerated and remove any objects which may present a safety hazard or damage the aerator (rocks, cans, etc.).

To prevent injury, do not operate aerator without cover in place. Do not make adjustments or perform any maintenance while tractor engine is running.

Do not leave tractor unattended without stopping the engine.

NOTE: Failure to lubricate aerating wheels can cause damage to axle, bushings and wheels.

Never cross hard objects or surfaces (sidewalks, driveways, stepping stones, etc.) with tines down.

Aerator should be raised completely out of the ground to avoid turf damage while turning.

Do not back up when tines are in the ground or damage to the tines and clamps may occur.

For maximum performance, a double set of tines may be mounted onto the aerating wheels. A longer screw is required for this application. To obtain this screw, order Part No. 311213.

- 1. Position tractor and aerator where you wish to begin aerating. On models with hydraulic lift, lower unit and begin aerating. On models with manual lift, use the lift handle (as stated in Step 7 on Page 7) to lower the aerator to the ground.
- 2. Tow Lawnaire over area to be aerated.
- 3. After completion of job, clean and service the aerator according to the following service instructions.

AWARNING

DO NOT use tractor hydraulics to support the aerator while servicing. Hydraulic lines may rupture causing unit to fall suddenly.

When replacement parts are required, use genuine Ryan parts or parts with equivalant characteristics including type, strength and material. Failure to do so may result in product malfunction and possible injury to the operator and/or bystanders.

LUBRICATION

- 1. Wipe off lubrication fittings before and after lubrication of aerating wheels. Lawnaire Model 544859A has six lubrication fittings; Lawnaire Models 544860A and 544876A have eight lubrication fittings.
- 2. Lubricate aerating wheels after every four hours of use. Use a standard lithium based grease.
- 3. Lubricate aerating wheels daily (Model 544860)
- 4. Transport wheel bearings should be repacked yearly using a good grade wheel bearing lubricant.

STORAGE INSTRUCTIONS

Thoroughly clean all tines, inside and out, after aerating is completed. A light coating of oil sprayed onto the tines or blades will help prevent rust and ensure proper coring the next time the unit is put into service.

Unit should be stored on boards to protect tines or blades from rust and damage. Store in a dry location.

Lubrication before long storage periods will help prevent moisture build-up in the lubrication cavities.

When bringing unit out of storage, check for loose hardware and damaged parts. Tighten and replace as needed.

FOR MODELS EQUIPPED WITH HYDRAULIC LIFT ACCESSORY

Check hydraulic cylinder for leaks and replace seal kit if needed. To obtain seal kit, order Part No. 884597.

Check the hydraulic hose connections for tightness and check the hoses for any wear or damage. Tighten and replace as necessary.

NOTE: Proper storage and maintenance will extend the usage and performance of the unit.

TINE WHEEL REPLACEMENT MODELS 544859A & 544876A

- 1. Attach aerator to tractor for stability.
- 2. Raise unit and place jackstands under frame assembly. Lower unit on frame making sure tines are not touching the floor.
- 3. Remove spirol pin (Part No. 64176-09) from axle, on side closest to wheel to be repaired.
- 4. Pull axle out until the tine wheel to be replaced or serviced is free. Note location of spacers as the tine wheels are removed.
- 5. Replace or service the appropriate tine wheel.
- 6. Remove any surface rust from axle shaft to prevent damage to seals.
- 7. Apply a lithium based lubricant to the axle shaft and to the lip of the seals before reassembling. Assemble in the reverse order of removal.
- 8. Replace spirol pin with new pin, Part No. 64176-09.

TINE WHEEL REPLACEMENT MODEL 544860A

- 1. Attach aerator to tractor for stability.
- 2. Raise unit and place jackstands under each frame arm and lower aerator, keeping the transport wheels and the tine wheels off the floor.
- 3. If aerator has the hydraulic lift accessory, disconnect the hydraulic cylinder from the wheel leg assembly.
- Remove spirol pin, wheel leg assembly and key from axle shaft, on side closest to wheel to be repaired. (Units with hydraulic lift will have a key at each end of axle shaft.)
- 5. Pull axle out until tine wheel to be replaced or serviced is free. Note the location of spacers as tine wheels are removed.
- 6. Remove any surface rust from the axle shaft to prevent damage to the seals.
- 7. Apply a lithium based lubricant to the axle shaft and to the lip of the seals before reassembling. Assemble in the reverse order of removal.
- 8. Replace spirol pin with new pin, Part No. 64176-09.

SPECIFICATIONS

Aerating Depth:

Up to 5" (127 mm), depending on soil condi-

tions

Model 544876A: Up to 4" (102 mm)

Aerating Pattern:

6" X 6" (152 mm X 152 mm)

Aerating Width:

36" (914 mm)

Model 544876A: 48" (1,219 mm)

Chassis:

1-1/2" sq. X 3/16" wall tube.

Dimensions:

Model 544859A:

Width 35" (889 mm) Height 34-1/2" (876 mm) Length 27-3/4" (705 mm)

Model 544876A:

Width 46" (1,368 mm) Height 34-1/2" (876 mm) Length 31" (787 mm)

Model 544860A:

Width 46" (1,168 mm) Height 31" (787 mm) Length 68-1/2" (1,740 mm)

Hitch:

Model 544859A: Mounted; 3-point hitch Model 544876A: 3-point hitch category "1" Model 544860A: Tow Behind; pin and clevis hitch.

Lubrication:

Pressure fittings. Refer to the service section on Page 10.

Tines:

See accessories section, Page 14.

Tires:

Model 544860A: 4.10/3.50-4, 2 ply pneu-

matic w/ball bearings.

Model 544860A: 10.25 X 3.25 semi-pneumatic. (SN1111111111 & up)

Tire Pressure:

Model 544860A: 40 p.s.i. (276 kPa)

Weight:

Model 544859A: 475 lbs. (215 kg) Model 544876A: 675 lbs. (306 kg) Model 544860A: 500 lbs. (227 kg)


Wheels:

Aerating; Cast iron with sintered bronze

bushing.

515196 - 1/2" Coring Tine 522361 - 3/4" Coring Tine, Thin Wall 515197 - 3/4" Coring Tine, Thick Wall


These tines are for use with aeration programs in the Spring and Fall. Soil cores up to 4" (102mm) in length can be removed with minimal surface disturbance.



(Single Knife Part Numbers) 521155 - Deep Slicing Knife 515193 - Shallow Slicing Knife

Slicing knives are used for aeration and renovation programs during all seasons. Slicing knives control thatch by cutting through grass runners and also have the advantage of no surface clean up after aerating. Knives are especially helpful in that they do not place buried seeds of noxious weeds on the surface where they can germinate.

Slicing knives are especially recommended for athletic fields. Slicing allows moisture, air and fertilizer to be absorbed while not creating hazardous playing conditions for athletes.




520404 - Aerating Tine

These tines are for turf building and Fall renovation programs. These tines will thoroughly open up the soil by penetrating deep into the ground bringing up large amounts of soil, which then becomes top dressing.




PARTS SECTION




ITEM	PART NO	. DESCRIPTION	QTY	ITEM	PART NO.	DESCRIPTION	QTY
1-1	64006-03	LOCKWASHER 3/8	4				
1-2	64123-82	SCREW-3/8-16 X 2-1/2	3				
1-3	64006-06	LOCKWASHER-7/16	4				
1-4	304364	NUT-7/16-14	4				
1-5	64025-05	NUT-3/8-16	4				
1-6	64123-39	SCREW-7/16-14 X 1	4				
1-7	64123-75	SCREW-3/8-16 X 3	1				
1-8	521905	SUPPORT-HOSE	1				
1-9	522090.7	BRKT-CYLINDER MOUNT	2				
1-10	545649.7	PIVOT-CYLINDER	1				
1-11	2703422	PIN-LOCK	2				
1-12	545787	CYLINDER-HYDRAULIC	1				
1-13	547741	PLATE-CLAMPING	1				
	(INCLUDES	S ITEM 14)					
1-14	521921	DECAL-INSTRUCTION	1				
1-15	64168-5	PIN-HAIR	2				
1-16	548390	FITTING-90 DEG. HYD 3/8-	18 2				
1-17	64164-35	KEY-WOODRUFF 1/4 X 2-1	/8 1				
1-18	64163-53	WASHER-SPECIAL	1				
1-19 *	884597	SEAL KIT-HYD CYLINDER	A/R				


^{*} NOT ILLUSTRATED




ITEM	PART NO	. DESCRIPTION	QTY	ITEM	PART NO.	DESCRIPTION	QTY
2-1	64006-03	LOCKWASHER-3/8	4				
2-2	64123-82	SCREW-3/8-16 X 2-1/2	4				
2-3	64025-05	NUT-3/8-16	4				
2-4	02-CP0510	PIN-COTTER 5/32 X 1-1/4	2				
2-5	521880	SPRING	2				
2-6	521892.7	HANDLE-LIFT	1				
2-7	521918	PIN-RETAINING	1				
2-8	2703422	PIN-LOCK	2				
2-9 *	545655.7	STOP-LEFT	1				
2-10	545675.7	STOP-RIGHT	1				
2-11	547741	PLATE-CLAMPING	1				
	(INCLUDE:	S ITEM 12)					
2-12	521921	DECAL-INSTRUCTION	1				
2-13	78011-1a	GRIP-HANDLE	1				
* NOT ILLUSTRATED							



ITEM	PART NO	DESCRIPTION	QTY	ITEM	PART NO	. DESCRIPTION	QTY
3-1	64152-23	SCREW-1/4-20 X 3/8 LG SP	10	3-40	4163401	COVER-ASSY	1
3-2		SCREW-3/8-16 X 2-1/2	13		(INCLUDE:	S ITEMS 1, 4, 30, 31, 32, & 41)
3-3		SCREW-3/8-16 X 1-1/2	4				
3-4		COVER-FILLER, 36"	1	3-41	835892	DECAL-DANGER	3
3-5		NUT-7/16-14	8				_
3-6		SCREW-3/8-16 X 1	2	3-42		FITTING-LUBRICATION	6
3-7		NUT-3/8-16	19	3-43	548256	SEAL-OIL	12
3-8		SCREW-3/8-16 X 2-1/4	96	3-44	-	NUT-3/8-16 FLANGELOCK	96
3-9		WASHER-3/8	6		827172	PIN-PIVOT	1
3-10		WASHER-7/16	8	3-46	822529	PIN-HAIR	2
3-11		SCREW-7/16-14 X 1-3/4	8				
	64176-09	PIN-SPIROL 1/4 X 1-3/4	2				
	515193	KNIFE-SHALLOW SLICING	48				
	515196	TINE-1/2 (13mm)	48				
	515197	TINE-3/4 (19mm)	48				
	515198	CLAMP-TINE	48		*OPTIO	NAL TINES AND KNIVES	
	519959	SPACER	2				
	520404	TINE-AERATING	48				
	521111	WASHER-1-5/16	2				
	521155	KNIFE-DEEP SLICING	48				
3-21	521879	SHAFT-AXLE	1				
3-22		ARM-FRAME	2				
3-23	64168-1	PIN-HAIR	2				
3-24	4163373.7		2				
3-25	522361	TINE-3/4 (19mm)	48				
	(STANDAR	D, SUPPLIED WITH UNIT)					
3-26	4163374.7	BRACKET-STOP	2				
3-27	4163369.7	FRAME	1				
3-28	4163365.2	MAST	1				
3-29	4163367.7	SUPPORT	1				
3-30	519842	DECAL-LUBRICATION	1				
3-31	4130431	LABEL-LAWNAIRE	2				
3-32	4130432	LABEL-RYAN OVAL, LARGE	3				
3-33	4163368.7	HITCH	2				
3-34	829987	SPACER-HITCH	2				
3-35	882933	PIN-HITCH	2				
3-36	64168-4	PIN-HAIR	2				
3-37	546048	WHEEL-TINE ASSY	6				
		S ITEMS 38 & 39)					
3-38	515184	BUSHING	2				
3-39	4163242	SPACER	1				



ITEM	PART NO	DESCRIPTION	QTY	ITEM	PART NO	. DESCRIPTION QTY
4-1	120177	LOCKWASHER-3/8	19	4-37	548256	SEAL-OIL 16
4-2	301431	SCREW-3/8-16 X 2-1/2	13	4-38	548804	NUT-3/8-16 FLANGELOCK 128
4-3	302600	SCREW-3/8-16 X 1-1/2	4	4-39	822529	PIN-HAIR 2
4-4	303269	LOCKWASHER-7/16	8	4-40	827172	PIN-PIVOT 1
4-5	304364	NUT-7/16-14	8	4-41	4161123	LABEL-RYAN OVAL, LARGE 3
4-6	306414	SCREW-3/8-16 X 1	2	4-42	4130431	LABEL-LAWNAIRE 2
4-7	306562	NUT-3/8-16	19			
4-8	306836	SCREW-3/8-16 X 2-1/4	128			
4-9	306981	WASHER-3/8	6			
4-10	311395	SCREW-7/16-14 X 1-3/4	8			
4-11	316945	PIN-SPIROL 1/4 X 1-3/4	2			
4-12	515193	KNIFE-SHALLOW SLICING	64		**	NOT ILLUSTRATED
4-13	515196	TINE-1/2 (13mm)	64			
4-14	515198	CLAMP-TINE	64			
4-15	519959	SPACER	4			
4-16	520404	TINE-AERATING	64			
4-17	521111	WASHER-1-5/16	2			
4-18	521155	KNIFE-DEEP SLICING	64			
4-19	521883	ARM-FRAME	2			
4-20	521917	PLATE	2			
4-21	522361	TINE-3/4 (19mm)	64			
4-22	523371	SHAFT-AXLE	1			
4-23	523498	BRACKET-STOP	2			
4-24	545646	MAST	1			
4-25	545647	SUPPORT	1			
4-26	545693	KIT-HITCH	2			
•		S ITEMS 27-29)	_			
4-27	829987	SPACER-HITCH	1			
4-28	882933	PIN-HITCH	1			
4-29	822529	PIN-HAIR	1			
			_			
4-30	546048	WHEEL-TINE ASSY S ITEMS 31 & 32)	6			
	(IINCLUDE)	5 11 EWIS 31 & 32)				
4-31	515184	BUSHING	2			
4-32	521814	SPACER	1			
4-33	547668	FRAME	1			
4-34	547721	COVER-ASSY	1			
	(INCLUDES		·			
4.05	005000	DEGAL BANGES				
4-35	835892	DECAL-DANGER	3			
4-36	548230	FITTING-LUBRICATION	8			



ITEM	PART NO.	DESCRIPTION	QTY	ITEM	PART NO	DESCRIPTION	QTY
5-1 5-2 5-3 5-4 5-5	64123-70 64152-23 64229-04	COVER-FILLER, 36" SCREW-3/8-16 X 1-1/2 SCREW-1/4-20 X 3/8 LG SP NUT-7/16-14 NUT-3/8-16	1 4 10 8 19	5-39 5-40 5-41 5-42	64141-4 835892 64229-03 53-186	NUT-3/8-16 FLANGELOCK DECAL-DANGER HANDS LOCKNUT-NYLON 3/8-16 WHEEL-10.25 X 3.25	96 3 2 2
5-6 5-7 5-8 5-9	64123-100 64163-61 64163-43	SCREW-3/8-16 X 2-1/4 WASHER-3/8 WASHER-7/16 SCREW-7/16-14 X 1-3/4 SPACER	96 4 8 8		55-112 53-187	ITEMS FOR HOOSIER TIRES BRG-ROLLER 5/8 ID X 1-3/8 RETAINER ITEMS FOR OTR TIRES)	,
5-11 5-12 * 5-13 * 5-14 *		PIN-SPIROL 1/4 X 1-3/4 KNIFE-SHALLOW SLICING TINE-1/2 (13mm) TINE-3/4 (19mm) CLAMP-TINE	2 48 48 48 48		4169687 4169688	· · · · · · · · · · · · · · · · · · ·	1
5-16 5-17 * 5-18 * 5-19	519959 520404 521155 64163-16 521883.7 521887 522361	SPACER TINE-AERATING KNIFE-DEEP SLICING WASHER ARM-FRAME SHAFT-AXLE TINE-3/4 (19mm) D, SUPPLIED WITH UNIT)	4 48 48 12 2 1 48		OI HOI	THES AND MIVES	
5-23 5-24 5-25 5-26 5-27 5-28 5-29 5-30	545677 521922 4161123 4130431 521921 546048	LEG-WHEEL	1 2 1 2 3 2 1 6				
5-31 5-32	515184 4163242	BUSHING SPACER	2 1				
5-33 5-34 5-35 5-36	4163401	FITTING-LUBRICATION SEAL-OIL KEY-WOODRUFF 1/4 X 1/8 COVER-ASSY S ITEMs 1, 3, 27, 28, 29, & 40)	6 12 2 1				
5-37 5-38	827248 64123-130	SPACER BLT-HEX 3/8-16X5-1/2	2 2				

