

ARTS MANUA

CALIFORNIA

Proposition 65 Warning

Diesel engine exhaust and some of its constituents are known to the State of California to cause cancer, birth defects and other reproductive harm.

A WARNING

The engine exhaust from this product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

CALIFORNIA

Proposition 65 Warning

Battery posts, terminals, wiring insulation, and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. WASH HANDS AFTER HANDLING.

IMPORTANT MESSAGE

Thank you for purchasing this Classen product. You have purchased a world class product, one of the best designed and built anywhere.

This product comes with Parts and Operator's Manuals. The useful life and good service you receive from this product depends to a large extent on how well you read and understand this manual. Treat this product properly and adjust it as instructed, and it will give you many years of reliable service.

See a Classen dealer for any service or parts needed. Classen service ensures that you continue to receive the best results possible from Classen products. You can trust Classen replacement parts because they are manufactured with the same high precision and quality as the original parts.

Classen designs and builds its equipment to serve many years in a safe and productive manner. For longest life, use this product only as directed in the manual, keep it in good repair and follow safety warnings and instructions. You'll always be glad you did.

Classen 1028 Street Road Southampton, PA 18966

TABLE OF CONTENTS	FIGURES	PAGE
SAFETY		
SET-UP, MAINTENANCE		
STORAGE		5
SPECIFICATIONS		6
PARTS SECTION		7
MAIN FRAME ASSEMBLY	FIGURE 1	
HANDLE & CUTTER ASSEMBLY		
POWER TRAIN ASSEMBLY	FIGURE 3	
KITS		
WARRANTY		

NOTICE !!!

Unauthorized modifications may present extreme safety hazards to operators and bystanders and could also result in product damage.

Classen strongly warns against, rejects and disclaims any modifications, add-on accessories or product alterations that are not designed, developed, tested and approved by Classen Engineering Department. Any Classen product that is altered, modified or changed in any manner not specifically authorized after original manufacture-including the addition of "after-market" accessories or component parts not specifically approved by Classen-will result in the Classen Warranty being voided.

Any and all liability for personal injury and/or property damage caused by any unauthorized modifications, add-on accessories or products not approved by Classen will be considered the responsibility of the individual(s) or company designing and/or making such changes. Classen will vigorously pursue full indemnification and costs from any party responsible for such unauthorized post-manufacture modifications and/or accessories should personal injury and/or property damage result.



This symbol means: ATTENTION! **BECOME ALERT!**

Your safety and the safety of others is involved.

Signal word definitions:

The signal words below are used to identify levels of hazard seriousness. These words appear in this manual and on the safety labels attached to Classen machines. For your safety and the safety of others, read and follow the information given with these signal words and/or the symbol shown above.

DANGER indicates an imminently hazardous situation which, if not avoided, WILL result in death or serious injury.

WARNING indicates a potentially hazardous situation which, if not avoided, COULD result in death or serious injury.

CAUTION indicates a potentially hazardous situation which, if not avoided, MAY result in minor or moderate injury. It may also be used to alert against unsafe practices or property damage.

CAUTION

CAUTION used without the safety alert symbol indicates a potentially hazardous situation which, if not avoided, MAY result in property damage

Schiller Grounds Care, Inc. SERIAL NUMBER

One Bobcat Lane Johnson Creek, WI 53038 U.S.A Phone: 920-699-2000 920-699-3683 Fox

MODEL NUMBER

MODEL NUMBER: This number appears on sales literature, technical manuals and price lists.

SERIAL NUMBER: This number appears only on your machine. It contains the model number followed consecutively by the serial number. Use this number when ordering parts or seeking warranty information.

MAINTENANCE SAFETY

In general

- Maintain machine according to manufacturer's schedule and instructions for maximum safety and best results.
- Park machine on level ground.
- Never allow untrained personnel to service machine.
- Guards should only be removed by qualified maintenance technician for maintenance/service. Replace when work is complete.
- Adjust or repair only after the engine has been stopped and the blade has stopped moving.
- Disconnect spark plug wire(s) before doing any maintenance.
- Replace parts if worn, damaged or faulty. For best results, always replace with parts recommended by the manufacturer.
- Do not dismantle the machine without releasing or restraining forces which may cause parts to move suddenly.
- Provide adequate support, e.g. jack stands for lifted machine or parts if working beneath.
- Do not put hands or feet near or under rotating parts.
- Clean up spilled oil or fuel thoroughly.
- Replace faulty mufflers.
- To reduce fire hazards, keep the engine, muffler, and fuel storage area free of grass, leaves, debris buildup or grease.

Blades

The sod cutter blade is sharp and can cut. Use extra caution when handling. Remove obstructions with care. Wrap the blade or wear gloves.



er

- Only replace blade. Nevstraighten or weld.
- Keep other persons away from blades.

Fuel

- Gasoline and diesel fuels are flammable; gasoline vapors are explosive. Use extra care when handling.
- Store only in containers specifically designed for fuel.





- When refueling or checking fuel level:
 - -Stop the engine and allow to cool;
 - -Do not smoke;
 - -Refuel outdoors only;
 - -Use a funnel;
 - -Do not overfill;

-If fuel is spilled, do not attempt to start the engine until the spill is cleaned up and vapors have cleared.

-Replace caps on fuel containers and tanks securely.

Sparks from static electricity can start fires or cause explosions. Flowing fuel can generate static electricity. To prevent static electricity sparks:

- Keep fuel containers electrically grounded. Do not fill containers in a vehicle or on a truck or trailer bed with a plastic liner. Fill containers on the ground away from the vehicle.
- When practical, remove petrol (gas) powered equipment from the truck or trailer and refuel it on the ground. If equipment must be refueled on the truck or trailer, refuel from a portable container rather than a dispenser nozzle.
- Keep the dispenser nozzle in contact with the rim of the fuel tank or container opening until fueling is complete. Do not use a nozzle lock-open device.

Storage Safety

- Stop the engine and allow to cool before storing.
- Drain the fuel tank outdoors only.
- Store fuel in an approved container in a cool, dry place.
- Keep the machine and fuel containers in a locked storage place to prevent tampering and to keep children from playing with them.
- Do not store the machine or fuel container near heating appliances with an open flame, such as a water heater, or an appliance with a pilot light.
- Keep gasoline (petrol) storage area free of grass, leaves and excessive grease to reduce fire hazard.
- Clean grass and debris from cutting units, drives, mufflers and engine to help prevent fires.

SET UP INSTRUCTIONS

To prevent injury, wear appropriate eye protection and stand clear when cutting banding. Banding is under tension and may snap back when cut.

- 1. Remove crate top, ends, sides and plastic covering the unit.. Remove the banding attaching the sod cutter to the pallet.
- 2. Roll the sod cutter off the pallet. The unit can also be driven off the pallet, but first read the Safety, Controls, and Operation sections of your manuals, then check the oil and add fuel.
- 3. Dispose of pallet, box, and banding in a responsible manner.

GENERAL MAINTENANCE

To keep the sod cutter in good operating condition, perform the following:

- Keep blade sharp; a sharp blade cuts cleaner, faster and more uniformly and places less load on the machine. Sharpen cutting edge on bevel or top side only.
- Keep drive belt at proper tension and free of oil and dirt at all times.
- Check engine oil level and air filter element daily.
- Check for loose bolts and connections.
- All grease fittings are pressurized type. Use a good grade Lithium Base Grease or equivalent. Grease eccentric arms sparingly every 4 hours of service, all others daily. Wipe off all grease fittings before and after each greasing (there are a total of 8 grease fittings).
- To make sure the chain on the front drive wheels is tight, you will need to remove the chain guard to check this. If tightening is required, loosen nuts and bolts on the 3/4" pillow block bearings and push the bearings toward the back of the sod cutter until chain is tight. Make sure both bearings go back evenly to keep jackshaft running even with the frame. After doing this, retighten nuts and bolts on the bearing and replace the chain guard.
- Engine (refer to manufacturer's owner's manual).

Engine Oil Level Check

- 1. BEFORE CHECKING OIL:
 - make certain the engine is level
- the engine switch is in the OFF position
- the sod cutter blade is NOT engaged
 - the drive wheels are disengaged.
- 2. Remove the filler cap/dipstick and wipe it clean.
- 3. Insert and remove the dipstick without screwing it into the filler neck. Check the oil level shown on the dipstick.
- If the oil level is low, fill to the edge of the oil filler hole with the recommended oil.
 SAE 10W-30 is recommended for general use.
 Refer to engine oil recommendations in engine manual for other viscosities and information.
- 5. Screw in the filler cap/dipstick securely.

Transmission Oil Level Check

- 1. Check the transmission oil level with the engine stopped and in a level position.
- 2. Remove the filler cap/dipstick and wipe it clean.
- 3. Insert and remove the dipstick without screwing it into the filler hole. Check the oil level shown on the dipstick.
- 4. If the oil level is low, add oil to reach the upper limit mark on the dipstick. Use the same oil that is recommended for the engine, SAE 10W-30.
- 5. Screw in the filler cap/dipstick securely.

STORAGE INSTRUCTIONS

WARNING

To prevent possible explosion or ignition of vaporized fuel, do not store equipment with fuel in tank or carburetor in enclosure with open flame (for example, a furnace or water heater pilot light).

Daily Storage

- 1. Check engine oil level and air filter element daily.
- 2. Check oil level in gear case. Hydro gear uses 20W50 oil.
- 3. Close fuel valve at bottom of fuel tank.
- 4. Clean cutting blade (grass, dirt, etc.).

Extended Storage

Before the equipment is put into storage for any period exceeding 30 days:

- 1. Drain all fuel from fuel tank and lines (use a hose or fuel line, routed from fuel tank shut-off to proper container).
- 2. Start engine and run until all fuel is used from the carburetor float bowl.
- 3. While engine is warm, check the transmission oil and refill with the proper weight of oil corresponding to the season when the equipment will next be used.
- 4. Remove the spark plug and squirt a small quantity of engine oil into the cylinder. Turn the engine over a few times to distribute the oil.
- 5. Lubricate all lubrication fittings.
- 6. Clean and oil cutting blade to prevent rust.

To put equipment into operation after an extended storage:

- 1. Fill fuel tank with clean fresh fuel.
- 2. Check crankcase oil level, and start engine.
- 3. Check fuel system for fuel leaks.

WARNING

When replacement parts are required, use genuine **Classen** parts or parts with equivalent characteristics, including type, strength and material. Failure to do so may result in product malfunction and possible injury to the operator and/or bystanders.

Carbon monoxide present in the exhaust is an odorless and deadly gas. Never start or run the engine inside where exhaust fumes can collect. Provide enough fresh air to keep fumes from getting too strong.

Replace any warning decal that becomes illegible immediately.



FOR MODELS with S/N 000101 & UP: SC-18SB


ENGINE Model4 cycle 5.5 H. P. Honda Model GX160
StarterRecoil Governor3400 RPM ± 200 RPM, no load Clutchspring loaded belt tightener type
REDUCTION Engine to blade
Engine to drive wheels57.2 to 1 WHEELS:
Drive8" (203 mm) Dia. w/knobby tread vulcanized to hub Rear8 x 1.75 (203 X 45mm)
semi-pneumatic tires CUTTING WIDTH: SC-1818"
GEAR CASE Lubrication20W50
Capacity31/2Pints(1.7L) CUTTING DEPTHup to 2-1/2"
BLADE PITCH Hand lever adjustmentvariable 0° to 9°
BLADE SPEED
DIMENSIONS
Width23" - For all, except SC-24 - 25"
Length
WEIGHT Dry Weights SC-18SB328 lbs.

PARTS SECTION

MAIN FRAME ASSEMBLY

SOD CUTTER

FIGURE 1



MAIN FRAME ASSEMBLY


SOD CUTTER

FIGURE 1

ITE	EM PART	NO.	DESCRIPTION	QTY	ITEM	PART NO.	DESCRIPTION	QTY
1	4172189	FRAME.	SOD CUTTER	1				
2	4170702	LARGE	GUARD	1				
3	C400267.17	INNER E	NGINE GUARD, 5.5 HP	1				
4	C400388.17	TRANS	IISION COVER, GEAR	1				
5	C400233.17	CHAIN C	GUARD	1				
6	C400232.17	SMALL (GUARD	1				
7	C500133		16-18 x 1	9				
8	C500140		16-18 x 3/4	5				
9	C500115		R, 5/16 LOCK	16				
	C500083		R, 5/16 FLAT	9				
	C500219		16-18 x 5	2				
	C500101	NUT, 5/1		2				
	C100017		WHEEL ASSEMBLY, 9X350X4	1				
	C500016		2" x 1-1/4" COTTER	2				
	C300002	PIN, AXL		1				
	C500154	,	8-16 x 2-1/2	1				
	C500146		8-16 x 1-1/2	1				
	C500042		R, 3/8" FLAT	15				
	C500130		R, 3/8 LOCK	8				
	C500129	NUT, 3/8		10				
	C300004.7		H. BELT ADJUSTMENT	1				
	C300134.7	CLIP, BE		1				
	C400236.17		R, 5.5 HP	-				
	C500134		8-16 x 1-1/4	5				
	C100021		G, BRASS	2				
	C500001		E FITTING, 1/4 x 28	8				
	C400114.7		1/2' BOLT, DUAL DRIVE	1 1				
	C300069.7	,						
	C100208 C100010	PULLEY	, DUAL DRIVE DOUBLE IDLER	2 2				
	C500091	BOLT, 3/		2				
	C500106	NUT, 1/2		1				
	C500006		R, 1/2 LOCK	1				
	4170316		CLASSEN	2				
	2000577		DANGER	1				
	C500142		" BOLT (SC-16, SC-20, SC-24)					
	C100131	DECAL,		2				
	C100504		ARRESTOR DECAL	1				
	C500133		" BOLT (SC-12)	12				
	C400011		DE ADAPTOR	2				
	C300417		DE ADAPTOR	2				
	C300047		DE ADAPTOR	2				
	C400188		DE ADAPTOR	2				
41	C500159	BOLT, 3/		1				
	C500041	,	-16 LOCK	2				
	C500043	BOLT, 3/		2				
44	C400010.7		ADE CLUTCH	1				

* NOT ILLUSTRATED

FIGURE 2



HANDLE ASSEMBLY

FIGURE 2

ITEI	M PART NO	D. DESCRIPTION	QTY	ITE	M PART NO	D. DESCRIPTION	QTY
1	C100007	GRIP, RUBBER	2	37	C200004.7	BOLT PITCH ADJUSTMENT	1
2	C100018	GRIP, L.H. HANDLE	2	38	C200005.7	BOLT, HEIGHT ADJUSTMENT	1
3	C100132	DECAL, CUTTER BLADE	1	39	C300039.7	PLATE, DEPTH GAUGE	1
4	C100133	DECAL, SLOW / FAST	1	40	C400001.7	BAR, HIEGHT ADJUSTMENT	1
5	C100134	DECAL, WHEEL DRIVE	1	41	C400238.17	PITCH ADJUSTMENT BAR	1
6	C100486	THROTTLE CONTROL & CABLE	1	42	C400444.7	WING NUT, DEPTH GAUGE	1
7	C300138.7	BRACE, HANDLE	1	43	C500006	WASHER, 1/2 LOCK	6
8	4172188	HANDLE, MAIN	1	44	C500007.7	NUT, 1/2 HANDLE	1
9	C400007.17	ARM, CUTTING BLADE ADJ	1	45	C500034	WASHER, 1/2 FLAT	8
10	C400008.17	HANDLE, ENGAGEMENT	2	46	C500088	WASHER, 1/4" FLAT	1
11	C400074.17	ARM, WHEEL DRIVE ADJ	1	47	C500106	NUT, 1/2-13	4
12	C400110.17	PIVOT ASSEMBLY	1	48	C500131	NUT, 1/2-13 LOCK	2
13	C500001	GREASE FITTING, 1/4 x 28	1	49	C500241	Bolt, 1/2-13 x 1-1/2	2
14	C500019	SPRING, SMALL HANDLE	2	50	C500151	BOLT, 1/2-13 X 1	2
15	C500025	NUT, 3/8-24	2	51	C500152	BOIt, 1/2-13 X 2-3/4	2
16	C500026	YOKE, 3/8 CLEVIS	2	52	C600001	STEEL SLEEVE	5
17	C500041	NUT, 3/8-16 LOCK	11	53	C800001.7	ARM, ECCENTRIC	2
18	C500042	WASHER, 3/8" FLAT	3	54	4172017	ARM, BLADE	2
19	C500043	BOLT, 3/8-16 X 1	7	55	C500136	NUT, 1/4-20	2
20	C500074	BOLT, 5/16-18 X 1-3/4	2	56	C500296	BOLT, 1/4-20 CRG	1
21	C500101	NUT, 5/16-18	12	57	C500068	NUT, 1/4-20 NYLOC	1
22	C500115	WASHER, 5/16 LOCK	10	58*	4164033	LABEL-CHF VERT	2
23	C500129	NUT, 3/8-16	6				
24	C500130	WASHER, 3/8 LOCK	6				
25	C500133	BOLT, 5/16-18 x 1	8				
26 27	C500134 C500137	BOLT, 3/8-16 x 1-1/4 WASHER, 1/4 LOCK	2 3				
28	C500137 C500139	NUT, 1/4-20 LOCK	3 4				
20 29	C500139	BOLT, 3/8-16 x 1-1/2	2			*NOT ILLUSTRATED	
29 30	C500154	BOLT, 3/8-16 x 2-1/2	2				
31	C500183	BOLT, 1/4-20 X 2	2				
32	C100001	WASHER, 3/4 NYLON	12				
33	C100002	SEAL	12				
34	C100003	BEARING	6				
35	C100007	GRIP, RUBBER	2				
36	C100016.7	BLADE, 18" SOD CUTTER	1				
	C100416	16" CUTTING BLADE	1				
	C100029	12" CUTTING BLADE	1				
	C100110	20" CUTTING BLADE	1				
	C100329	24" CUTTING BLADE	1				
	-						

POWER TRAIN ASSEMBLY

SOD CUTTER

FIGURE 3




FIGURE 3

ITEM	PART N	O. DESCRIPTION	QTY	ITEM	PART N	0.	DES
1	C100004	BEARING 1" PILLOW BLOCK	4	43	C500154	BOLT,	3/8-16
2	C100005	ENGINE, 5.5 H.P. HONDA	1	44	C500157	BOLT,	1/4-20
3	C100008	REDUCTION BOX	1	45	C500158	BOLT,	1/2-13
4	C100010	PULLEY, IDLER	2	46	C500159	BOLT,	3/8-16
5	C100011	V-BELT, BX31 DRIVE	2	47	C500174	BOLT,	1/2-13
6	C100013	BEARING 3/4" PILLOW BLOCK	2	48	C500181		/4 x 1-
7	C100022	PULLEY, TAPER LOCK	1	49	C600003		T, ECC
8	C100023	HUB, TAPER LOCK	1	50	4171051		T, 12" [
9	C100024	V-BELT, B B56 ENGINE 5.5HP	1	51	C700002.7		
10	C100025	LINK, #40 CONNECTING	1	52*	C100244		EL, WI
11	C100026	V-BELT 6934 BELT	1	53	C500079		3/8-16
12	C100027	SPRING, THROTTLE	1	54	64164-51	KEY-S	Q 1/4
13	C100028	PULLEY W/ HUB & BOLTS	1				
14	C100207	SHEAVE, DUAL DRIVE DBLE V	1		*NOT ILLUS	STRATE	ED
15	C100208	PULLEY, DRIVE DBLE IDLER	1				
16	C100307	CHAIN, 58 ROLLERS	1				
17	C200001	SPROCKET W/HUB, SHAFT	1				
18	C200002	PULLEY W/HUB & BOLTS, 6"	1				
19	C200031	PULLEY, DUAL DRIVE 5" SPLIT					
20	C300001	SPACER, DRIVE SHAFT	1				
21		CLIP, R.H. BELT ADJUSTMENT	1				
22		CLIP, BELT L.H.	1				
23	C200039	JACK SHAFT	1				
24	C500003	KEY, 1/4 x 7/8 HALF MOON	2 2				
25	C500004	KEY, 1/4 x 1 SQUARE					
26	C500006	WASHER, 1/2 LOCK	17				
27 28	C500240	KEY, 3/16 X 1 1/2	1				
20 29	C500029	BOLT, 1/4-20 x 3/4	2 8				
29 30	C500034 C500042	WASHER, 1/2 FLAT WASHER, 3/8" FLAT	o 18				
31	C700024	WHEEL, 8-5/8" DRIVE	4				
32	C500083	WASHER, 5/16 FLAT	8				
33	C500091	BOLT, 3/8-16 x 2	2				
34	C500091	NUT, 5/16-18	8				
35	C500106	NUT, 1/2-13	17				
36	C500115	WASHER, 5/16 LOCK	8				
37	C500129	NUT, 3/8-16	11				
38	C500130	WASHER, 3/8 LOCK	17				
39	C500137	WASHER, 1/4 LOCK	4				
40	C500139	NUT, 1/4-20 LOCK	4				
41	C500133	BOLT, 3/8-16 x 1-1/2	5				
42	C500140	BOLT, 5/16-18 x 1-1/2	8				
	2000.11		Ŭ				

ITEM	PART N	D. DESCRIPTION	QTY
43	C500154	BOLT, 3/8-16 x 2-1/2	1
44	C500157	BOLT, 1/4-20 x 3-1/2	2
45	C500158	BOLT, 1/2-13 x 3-1/2	8
46	C500159	BOLT, 3/8-16 X3	1
47	C500174	BOLT, 1/2-13 x 1-3/4	8
48	C500181	KEY, 1/4 x 1-1/2 SQUARE	2
49	C600003	SHAFT, ECCENTRIC	1
50	4171051	SHAFT, 12" DRIVE	1
51	C700002.7	HUB, ECCENTRIC	2
52*	C100244	SWIVEL, WIRE	1
53	C500079	BOLT, 3/8-16 x 1-3/4	4
54	64164-51	KEY-SQ 1/4 X 1-1/4 ROUNDED	2

OPTIONAL KITS (NOT SHOWN ON PARTS ILLUSTRATIONS)

KIT P/N	DESCRIPTION	
C100076	ELECTRICAL SHUT-OFF SWITCH & HARDWARE	
C400037	SET OF 2 SIDE BUMPERS & HARDWARE	

SOD CUTTER			
SOD COTTER			

CLASSEN®

2 YEAR LIMITED SERVICE AND WARRANTY POLICY

Schiller Grounds Care, Inc. 1028 Street Road • Southampton, PA 18966 Telephone: 1-877-596-6337

TWO YEAR LIMITED WARRANTY

EffectiveJanuary 1, 2015

For the period of two years from the date of purchase, CLASSEN will repair or replace for the original purchaser free of charge, any part or parts found upon the examination of our factory authorized service station, or by the factory in Southampton, PA to be defective in material or workmanship. All transportation charges on parts submitted for repair or replacement under this warranty shall be borne by the purchaser.

This warranty does not include engines or engine parts, tires, batteries, or gearboxes that are covered under separate warranties furnished by their manufacturer or supplier, nor does it include normal maintenance parts, including but not limited to, spark plugs, points, filters, blades, and lubricants.

All service under this warranty will be furnished or performed by our factory authorized service stations.

There is no other expressed warranty. Implied warranties, including those of merchantability and fitness for a particular purpose, are limited to two years from the date of purchase and to the extent permitted by law, any and all implied warranties are excluded. The above remedy of repair and replacement of defective parts is the purchaser's exclusive remedy for any defect, malfunction or breach of warranty. Liability for incidental or consequential damages under any and all warranties is excluded to the extent permitted by law.

NORMAL RESPONSIBILITIES OF THE SELLER AND THE USER

- 1. The Distributor or Dealer is responsible for the proper assembly and preparation of the product for delivery to the end user.
- 2. The User is responsible for reading the Manual and Instructions.
- 3. The User is responsible for proper operation and maintenance as described in the manual.
- 4. The User is responsible for the replacement of wear items such as blades, belts, tires, batteries, etc.
- 5. The User is responsible for damage due to improper operation and maintenance, as well as abuse.

All claims must be received by the factory 30 days after the end of the warranty period to receive warranty consideration.

CLASSEN® SCHILLER GROUNDS CARE, INC. 1028 STREET ROAD, P.O. BOX 38 SOUTHAMPTON, PA 18966 PHONE 877-596-6337 • FAX 215-357-8045