

FOR MODELS with S/N 000101 & UP:

SC-12/5.5E	SC-12/8.0E
SC-16/5.5E	SC-16/8.0E
SC-18/5.5E	SC-18/8.0E
SC-20/5.5E	SC-20/8.0E
SC-24/5.5E	SC-24/8.0E





OPERATORS MANUAL C100595

CALIFORNIA Proposition 65 Warning

Diesel engine exhaust and some of its constituents are known to the State of California to cause cancer, birth defects and other reproductive harm.

A WARNING

The engine exhaust from this product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

CALIFORNIA Proposition 65 Warning

Battery posts, terminals, wiring insulation, and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. WASH HANDS AFTER HANDLING.

IMPORTANT MESSAGE

Thank you for purchasing this Classen product. You have purchased a world class product, one of the best designed and built anywhere.

This product comes with Parts and Operator's Manuals. The useful life and good service you receive from this product depends to a large extent on how well you read and understand this manual. Treat this product properly and adjust it as instructed, and it will give you many years of reliable service.

See a Classen dealer for any service or parts needed. Classen service ensures that you continue to receive the best results possible from Classen products. You can trust Classen replacement parts because they are manufactured with the same high precision and quality as the original parts.

Classen designs and builds its equipment to serve many years in a safe and productive manner. For longest life, use this product only as directed in the manual, keep it in good repair and follow safety warnings and instructions. You'll always be glad you did.

Classen 1028 Street Road Southampton, PA 18966

TABLE OF CONTENTS SAFETY	FIGURES	PAGE 2, 3
SET-UP, MAINTENANCE		4
STORAGE		5
SPECIFICATIONS		6
PARTS SECTION		7
MAIN FRAME ASSEMBLY	FIGURE 1	8, 9
HANDLE & CUTTER ASSEMBLY	FIGURE 2	10, 11
POWER TRAIN ASSEMBLY	FIGURE 3	12, 13
KITS		
WARRANTY		. BACK COVER

11-2013 **1**

NOTICE !!!

Unauthorized modifications may present **extreme** safety hazards to operators and bystanders and could also result in product damage.

Classen strongly warns against, rejects and disclaims any modifications, add-on accessories or product alterations that are not designed, developed, tested and approved by Classen Engineering Department. Any Classen product that is altered, modified or changed in any manner not specifically authorized after original manufacture—including the addition of "after-market" accessories or component parts not specifically approved by Classen—will result in the Classen Warranty being voided.

Any and all liability for personal injury and/or property damage caused by any unauthorized modifications, add-on accessories or products not approved by Classen will be considered the responsibility of the individual(s) or company designing and/or making such changes. Classen will vigorously pursue full indemnification and costs from any party responsible for such unauthorized post-manufacture modifications and/or accessories should personal injury and/or property damage result.



This symbol means:

ATTENTION! BECOME ALERT!

Your safety and the safety of others is involved.

Signal word definitions:

The signal words below are used to identify levels of hazard seriousness. These words appear in this manual and on the safety labels attached to Classen machines. For your safety and the safety of others, read and follow the information given with these signal words and/or the symbol shown above.

A DANGER

DANGER indicates an imminently hazardous situation which, if not avoided, **WILL** result in death or serious injury.

AWARNING

WARNING indicates a potentially hazardous situation which, if not avoided, **COULD** result in death or serious injury.

ACAUTION

CAUTION indicates a potentially hazardous situation which, if not avoided, **MAY** result in minor or moderate injury. It may also be used to alert against unsafe practices or property damage.

CAUTION

CAUTION used without the safety alert symbol indicates a potentially hazardous situation which, if not avoided, **MAY** result in property damage

Schiller Grounds Care, Inc.

Ine Bobcat LaneJohnson Creek, WI 53038 U.S.APhone: 920-699-2000Fax: 920-699-3683

MODEL NUMBER

SERIAL NUMBER

MODEL NUMBER: This number appears on sales literature, technical manuals and price lists.

SERIAL NUMBER: This number appears only on your machine. It contains the model number followed consecutively by the serial number. Use this number when ordering parts or seeking warranty information.

MAINTENANCE SAFETY

In general

- Maintain machine according to manufacturer's schedule and instructions for maximum safety and best results.
- Park machine on level ground.
- Never allow untrained personnel to service machine.
- Guards should only be removed by qualified maintenance technician for maintenance/service.
 Replace when work is complete.
- Adjust or repair only after the engine has been stopped and the blade has stopped moving.
- Disconnect spark plug wire(s) before doing any maintenance.
- Replace parts if worn, damaged or faulty. For best results, always replace with parts recommended by the manufacturer.
- Do not dismantle the machine without releasing or restraining forces which may cause parts to move suddenly.
- Provide adequate support, e.g. jack stands for lifted machine or parts if working beneath.
- Do not put hands or feet near or under rotating parts.
- Clean up spilled oil or fuel thoroughly.
- Replace faulty mufflers.
- To reduce fire hazards, keep the engine, muffler, and fuel storage area free of grass, leaves, debris buildup or grease.

Blades

The sod cutter blade is sharp and can cut. Use extra caution when handling. Remove obstructions with care. Wrap the blade or wear gloves.



 Only replace blade. Nevstraighten or weld.

Keep other persons away from blades.

Fuel

- Gasoline and diesel fuels are flammable; gasoline vapors are explosive. Use extra care when handling.
- Store only in containers specifically designed for fuel.





- When refueling or checking fuel level:
 - -Stop the engine and allow to cool;
 - -Do not smoke;
 - -Refuel outdoors only;
 - -Use a funnel;
 - -Do not overfill;
 - -If fuel is spilled, do not attempt to start the engine until the spill is cleaned up and vapors have cleared.
 - -Replace caps on fuel containers and tanks securely.

Sparks from static electricity can start fires or cause explosions. Flowing fuel can generate static electricity. To prevent static electricity sparks:

- Keep fuel containers electrically grounded. Do not fill containers in a vehicle or on a truck or trailer bed with a plastic liner. Fill containers on the ground away from the vehicle.
- When practical, remove petrol (gas) powered equipment from the truck or trailer and refuel it on the ground. If equipment must be refueled on the truck or trailer, refuel from a portable container rather than a dispenser nozzle.
- Keep the dispenser nozzle in contact with the rim of the fuel tank or container opening until fueling is complete. Do not use a nozzle lock-open device.

Storage Safety

- Stop the engine and allow to cool before storing.
- Drain the fuel tank outdoors only.
- Store fuel in an approved container in a cool, dry place.
- Keep the machine and fuel containers in a locked storage place to prevent tampering and to keep children from playing with them.
- Do not store the machine or fuel container near heating appliances with an open flame, such as a water heater, or an appliance with a pilot light.
- Keep gasoline (petrol) storage area free of grass, leaves and excessive grease to reduce fire hazard.
- Clean grass and debris from cutting units, drives, mufflers and engine to help prevent fires.

SET UP INSTRUCTIONS

To prevent injury, wear appropriate eye protection and stand clear when cutting banding. Banding is under tension and may snap back when cut.

- 1. Remove crate top, ends, sides and plastic covering the unit.. Remove the banding attaching the sod cutter to the pallet.
- 2. Roll the sod cutter off the pallet. The unit can also be driven off the pallet, but first read the Safety, Controls, and Operation sections of your manuals, then check the oil and add fuel.
- 3. Dispose of pallet, box, and banding in a responsible manner.

GENERAL MAINTENANCE

To keep the sod cutter in good operating condition, perform the following:

- Keep blade sharp; a sharp blade cuts cleaner, faster and more uniformly and places less load on the machine. Sharpen cutting edge on bevel or top side only.
- Keep drive belt at proper tension and free of oil and dirt at all times.
- Check engine oil level and air filter element daily.
- Check for loose bolts and connections.
- All grease fittings are pressurized type. Use a good grade Lithium Base Grease or equivalent.
 Grease eccentric arms sparingly every 4 hours of service, all others daily. Wipe off all grease fittings before and after each greasing (there are a total of 8 grease fittings).
- To make sure the chain on the front drive wheels is tight, you will need to remove the chain guard to check this. If tightening is required, loosen nuts and bolts on the 3/4" pillow block bearings and push the bearings toward the back of the sod cutter until chain is tight. Make sure both bearings go back evenly to keep jackshaft running even with the frame. After doing this, retighten nuts and bolts on the bearing and replace the chain guard.
- Engine (refer to manufacturer's owner's manual).

Engine Oil Level Check

- 1. BEFORE CHECKING OIL:
 - make certain the engine is level
- the engine switch is in the OFF position
- the sod cutter blade is NOT engaged
- the drive wheels are disengaged.
 - 2. Remove the filler cap/dipstick and wipe it clean.
 - Insert and remove the dipstick without screwing it into the filler neck. Check the oil level shown on the dipstick.
 - 4. If the oil level is low, fill to the edge of the oil filler hole with the recommended oil. SAE 10W-30 is recommended for general use. Refer to engine oil recommendations in engine manual for other viscosities and information.
 - 5. Screw in the filler cap/dipstick securely.

Transmission Oil Level Check

- 1. Check the transmission oil level with the engine stopped and in a level position.
- 2. Remove the filler cap/dipstick and wipe it clean.
- 3. Insert and remove the dipstick without screwing it into the filler hole. Check the oil level shown on the dipstick.
- 4. If the oil level is low, add oil to reach the upper limit mark on the dipstick. Use the same oil that is recommended for the engine, SAE 10W-30.
- 5. Screw in the filler cap/dipstick securely.

STORAGE INSTRUCTIONS

▲WARNING

To prevent possible explosion or ignition of vaporized fuel, do not store equipment with fuel in tank or carburetor in enclosure with open flame (for example, a furnace or water heater pilot light).

Daily Storage

- 1. Check engine oil level and air filter element daily.
- 2. Check oil level in gear case. Hydro gear uses 20W50 oil.
- 3. Close fuel valve at bottom of fuel tank.
- 4. Clean cutting blade (grass, dirt, etc.).

Extended Storage

Before the equipment is put into storage for any period exceeding 30 days:

- 1. Drain all fuel from fuel tank and lines (use a hose or fuel line, routed from fuel tank shut-off to proper container).
- 2. Start engine and run until all fuel is used from the carburetor float bowl.
- While engine is warm, check the transmission oil and refill with the proper weight of oil corresponding to the season when the equipment will next be used.
- 4. Remove the spark plug and squirt a small quantity of engine oil into the cylinder. Turn the engine over a few times to distribute the oil.
- 5. Lubricate all lubrication fittings.
- 6. Clean and oil cutting blade to prevent rust.

To put equipment into operation after an extended storage:


- 1. Fill fuel tank with clean fresh fuel.
- 2. Check crankcase oil level, and start engine.
- 3. Check fuel system for fuel leaks.

AWARNING

When replacement parts are required, use genuine **Classen** parts or parts with equivalent characteristics, including type, strength and material. Failure to do so may result in product malfunction and possible injury to the operator and/or bystanders.

Carbon monoxide present in the exhaust is an odorless and deadly gas. Never start or run the engine inside where exhaust fumes can collect. Provide enough fresh air to keep fumes from getting too strong.


Replace any warning decal that becomes illegible immediately.



FOR MODELS with S/N 000101 & UP:


SC-12/5.5E SC-16/5.5E SC-18/5.5E SC-20/5.5E SC-24/5.5E	SC-12/8.0E SC-16/8.0E SC-18/8.0E SC-20/8.0E SC-24/8.0E
ENGINE Model4 cycle 5.5 H. P. Honda	CUTTING DEPTHup to 2-1/2"
Model GX160	DI ADE DITOU
Wodel GX100	BLADE PITCH Hand lever adjustmentvariable 0° to 9°
4 cycle 8 HP Honda	Hand lever adjustifiertvariable 0 to 9
Model GX240	BLADE SPEED1188 RPM @ 3400 engine RPM
StarterRecoil	DIMENSIONS
Governor3400 RPM ± 200 RPM, no load	Width23" - For all, except SC-24 - 25"
Clutchspring loaded belt tightener type	Length59"
. 0	Height35"
REDUCTION	Wheel Base22"
Engine to blade3.03 to1	
Engine to drive wheels57.2 to 1	WEIGHT
	Dry Weights
WHEELS:	SC-12/5.5318 lbs.
Drive8" (203 mm) Dia. w/knobby	SC-12/8342 lbs.
tread vulcanized to hub	SC-16/5.5324 lbs.
Rear8 x 1.75 (203 X 45mm)	SC-16/8348 lbs.
semi-pneumatic tires	SC-18/5.5328 lbs.
CUTTING WIDTH:	SC-18/8352 lbs.
SC-1211-3/4"	SC-20/5.5329 lbs,
SC-1616"	SC-20/8353 lbs.
SC-18	SC-24/8355 lbs.
SC-20	
SC-2424"	
GEAR CASE	
Lubrication20W50	
Capacity31/2Pints(1.7L)	


PARTS SECTION




ITE	M PART N	IO.	DESCRIPTION	QTY	ITEM	PART NO.	DESCRIPTION	QTY
1	4172186	FRAME	E, SOD CUTTER	1				
2	4171984	LARGE	GUARD	1				
3	C400267.17	INNER	ENGINE GUARD, 5.5 HP	1				
	C400268.17		ENGINE GUARD, 8.0 HP					
4	C400388.17	TRANS	SMISION COVER, GEAR	1				
5	4173101.17	CHAIN	GUARD	1				
6	4173102.17		. GUARD	1				
7	C500133	-	5/16-18 x 1	9				
8	C500140		5/16-18 x 3/4	5				
9	C500115		ER, 5/16 LOCK	16				
10	C500083		ER, 5/16 FLAT	9				
11	C500219		5/16 x 5	2				
12	C500101	NUT, 5		2				
13	C100017		WHEEL ASSEMBLY, 9X350X4					
14	C500016	-	32" x 1-1/4" COTTER	2				
15	C300002	PIN, A		1				
16	C500154		3/8-16 x 2-1/2	1				
17	C500146		3/8-16 x 1-1/2	1				
18	C500042		ER, 3/8" FLAT	15				
19	C500130		ER, 3/8 LOCK	8				
20	C500129	NUT, 3		10				
21	C300004.7		R.H. BELT ADJUSTMENT	1				
22	C300134.17		BELT L.H.	1				
23	C400237.17		ER, 8.0 HP	1				
24	C500134	-	3/8-16 x 1-1/4	5				
25	C100021		NG, BRASS	2				
26	C500001		SE FITTING, 1/4 x 28	8				
27	C400114.7		V/ 1/2' BOLT, DUAL DRIVE	1				
28	C300069.7		DRIVE LINKAGE	1				
29	C100208		Y, DUAL DRIVE DOUBLE IDLE					
30	C100010		Y, IDLER	2				
31	C500091		3/8-16 x 2	2				
32	C500106	NUT, 1		1				
33	C500006		ER, 1/2 LOCK	1				
34	4170316		., CLASSEN	2				
35	C100506		., CE SERVICE BELTS	3				
36	C500142		2" BOLT (SC-16, SC-20, SC-2					
37	C100262		-, "SC-12"	2				
	C100417		_ , "SC-16"	2				
	C100131		_ , "SC-18"	2				
	C100260		_ , "SC-20"	2				
00	C100345		_ , "SC-24"	2				
38	C100504		(ARRESTOR DECAL	1				
39	C500133		1" BOLT (SC-12)	12				
40	C400011		ADE ADAPTOR	2				
	C300417		ADE ADAPTOR	2				
	C300047		ADE ADAPTOR	2				
4.4	C400188		ADE ADAPTOR	2				
41	C500159		3/8-16 X3	1				
42	C500041		/8-16 LOCK	2				
43	C500043	,	3/8-16 X 1	2				
44 45*	C400010.7		BLADE CLUTCH	1				
45*	C100607	DECAL	., 12 DEGREES WARNING	1				

^{*} NOT ILLUSTRATED





ITEI	M PART NO	. DESCRIPTION	QTY	ITEN	PART NO	. DESCRIPTION	QTY
1	C100007	GRIP, RUBBER	4	37	C200004.7	BOLT PITCH ADJUSTMENT	1
2	C100018	GRIP, L.H. HANDLE	2	38	C200005.7	BOLT, HEIGHT ADJUSTMENT	1
3	4173087.17	THROTTTLE FRICTION BRCKT	1	39	C300039.17	PLATE, DEPTH GAUGE	1
4	4173112	GROMMET	1	40	C400001.7	BAR, HIEGHT ADJUSTMENT	1
5	64123-330	BOLT, 1/4 x 2-1/2	1	41	C400238.7	PITCH ADJUSTMENT BAR	<u>1</u>
6	C100486	THUMB THROTTLE CONTROL	1	42	4172692	KNOB-PLASTIC	1
7	C300138.17	BRACE, HANDLE	1	43	C500006	WASHER, 1/2 LOCK	4
8	4172183	HANDLE, MAIN	1	44	C500007.7	NUT, 1/2 HANDLE	1
9	C400007.17	ARM, CUTTING BLADE ADJUST	T 1	45	C500034	WASHER, 1/2 FLAT	8
10	C400008.17	HANDLE, ENGAGEMENT	2	46	C500088	WASHER, 1/4" FLAT	1
11	C400074.17	ARM, WHEEL DRIVE ADJUST	1	47	C500106	NUT, 1/2-13	4
12	C400110.17	PIVOT ASSEMBLY	1	48	C500131	NUT, 1/2-13 LOCK	2
13	C500001	GREASE FITTING, 1/4 x 28	1		C500241	Bolt, 1/2-13 x 1	2
14	C500019	SPRING, SMALL HANDLE	2		C500249	BOLT, 1/2 x 1 FINE THREAD	2
15	C500025	NUT, 3/8-24	2	51	C500152	BOlt, 1/2-13 X 2-3/4	2
16	C500026	YOKE, 3/8 CLEVIS	2	52	C600001	STEEL SLEEVE	4
17	C500041	NUT, 3/8-16 LOCK	11	53	C400411.7	ARM, ECCENTRIC	2
18	C500042	WASHER, 3/8" FLAT	3	1	4172185	ARM, BLADE	2
19	C500043	BOLT, 3/8-16 X 1	7		C500136	NUT, 1/4-20	6
20	C500074	BOLT, 5/16-18 X 1-3/4	2	56	C500296	BOLT, 1/4-20 CRG	1
21	C500101	NUT, 5/16-18	8	1	C500068	NUT, 1/4-20 NYLOC	3
22	C500115	WASHER, 5/16 LOCK	12	58	C500272	WASHER, 1/2" EXT. LOCK	4
23	C500129	NUT, 3/8-16	6	1	C400412.7	WASHER, STEEL ENHANCED	4
24	C500130	WASHER, 3/8 LOCK	6	60	C100626	WASHER, PLASTIC	4
25	C500133	BOLT, 5/16-18 x 1	2	1	C100265	BEARING, ENHANCED	2
26	C500134	BOLT, 3/8-16 x 1-1/4	2	62	C100508	DECAL, CE CONTROL PANEL	1
27	C500137	WASHER, 1/4 LOCK	3	1	4163589	LABEL-CHF VERT EU	2
28	C500139	NUT, 1/4-20 LOCK	4		64123-329	BOLT, 5/16-18 x 1	6
29	C500146	BOLT, 3/8-16 x 1-1/2	2	1	64025-51	NUT-HEX 5/16-24	6
30	C500154	BOLT, 3/8-16 x 2-1/2	2	66	4173113	SPRING-COMPRESSION	1
31	64123-311	BOLT, 1/4-20 X 3-1/4	2				
32	C100001	WASHER, 3/4 NYLON	8				
33	C100002	SEAL	8				
34	C100003	BEARING	4				
35	C500183	BOLT 1/4-20 x 2	1				
36	C100016.7	BLADE, 18" SOD CUTTER	1				
	C100416.7	16" CUTTING BLADE	1			*NOT ILLUSTRATED	
	C100029.7	12" CUTTING BLADE	1				
	C100110.7	20" CUTTING BLADE	1				
	C100329.7	24" CUTTING BLADE	1				



ITEN	/ PART N	IO. DESCRIPTION	QTY	ITEM	PART NO	O. DESCRIPTION	QTY
1	C100004	BEARING 1" PILLOW BLOCK	4	37	C500129	NUT, 3/8-16	11
2	C100005	ENGINE, 5.5 H.P. HONDA	1	38	C500130	WASHER, 3/8 LOCK	17
	C100114	ENINGE, 8.0 H.P. HONDA		39	C500137	WASHER, 1/4 LOCK	4
	B222522	DEFLECTOR, MUFFLER	1	40	C500139	NUT, 1/4-20 LOCK	4
	64152-84	SCREW-8-15X3/8 HEX WSHR	2	41	C500146	BOLT, 3/8-16 x 1-1/2	5
				42	C500147	BOLT, 5/16-18 x 1-1/2	8
3	C100008	REDUCTION BOX	1	43	C500154	BOLT, 3/8-16 x 2-1/2	1
4	C100010	PULLEY, IDLER	2	44	64164-51	KEY-1/4 X 1-1/4 ROUNDED	2
5	C100011	V-BELT, BX31 DRIVE	2	45	C500158	BOLT, 1/2-13 x 3-1/2	8
6	C100013	BEARING 3/4" PILLOW BLOCK	2	46	C500159	BOLT, 3/8-16 X3	1
7	C100022	PULLEY, TAPER LOCK	1	47	C500174	BOLT, 1/2-13 x 1-3/4	8
8	C100023	HUB, TAPER LOCK	1	48	C500181	KEY, 1/4 x 1-1/2 SQUARE	2
9	C100024	V-BELT, B B56 ENGINE 5.5HP	1	49	C600003	SHAFT, ECCENTRIC	1
	C100113	B59 V-BELT, 8.0HP MODEL	1	50	4171051	SHAFT, 12" DRIVE	1
10	C100025	LINK, #40 CONNECTING	1	51	C700035.7	HUB, ECCENTRIC	2
11	C100026	V-BELT 6934 BELT	1	52*	C100244	SWIVEL, WIRE	1
12	C100027	SPRING, THROTTLE	1	53	C500079	BOLT-, 3/816 X 1-3/4	4
13	C100028	PULLEY W/ HUB & BOLTS,	1	54	C500064	SET SCREW 5/16-18 X3/8	1
14	C100207	SHEAVE, DUAL DRIVE	1	55	64123-114	BLT-HEX 1/4-20 X 18	2
	C100014	SHEAVE, SINGLE DRIVE (SC-12) 1				
15	C100208	PULLEY, DUAL DRIVE IDLER	1				
16	C100307	CHAIN, 58 ROLLERS	1				
17	C200001	SPROCKET W/HUB, SHAFT	1		*NOT ILLUS	STRATED	
18	C200002	PULLEY W/HUB & BOLTS, 6"	1				
19	C200031	PULLEY, DUAL DRIVE 5" SPLIT	1				
20	C300001	SPACER, DRIVE SHAFT	1				
21	C300004	CLIP, R.H. BELT ADJUSTMENT	1				
22	C300134	CLIP, BELT L.H.	1				
23	C200039	JACK SHAFT W/SPROCKET	1				
24	C500003	KEY, 1/4 x 7/8 HALF MOON	2				
25	C500004	KEY, 1/4 x 1 SQUARE	2				
26	C500006	WASHER, 1/2 LOCK	17				
27	C500240	KEY, 3/16 X 1 1/2	1				
28	C500029	BOLT, 1/4-20 x 3/4	2				
29	64163-67	WSHR516X1X12GA	8				
30	C500042	WASHER, 3/8" FLAT	18				
31	C700024	WHEEL, 8-5/8" DRIVE	4				
32	C500083	WASHER, 5/16 FLAT	8				
33	C500091	BOLT, 3/8-16 x 2	2				
34	C500101	NUT, 5/16-18	8				
35	C500106	NUT, 1/2-13	17				
36	C500115	WASHER, 5/16 LOCK	8				

CE REQUIRED KITS (NOT SHOWN ON PARTS ILLUSTRATIONS)

KIT P/N	DESCRIPTION	
C400322.7	CE MUFFLER GUARD & HARDWARE, HONDA GX120/GX160	(USED ON 5.5HP HONDA ENGINES ONLY)
C400323.7	CE MUFFLER GUARD & HARDWARE, HONDA GX240	(USED ON 8.0HP ENGINES ONLY)
B222522	MUFFLER GUARD-5.5HP B&S	
C400324	CE GEAR DRIVE GUARDS-5.5HP	
C400325	CE GEAR DRIVE GUARDS-8.0HP	
C400269.17	L.H. HANDLE GUARD W/ RUBBER & HARD- WARE	
C400270.17	R.H. HANDLE GUARD W/ RUBBER & HARD- WARE	
C400271.17	THROTTLE FRICTION BRACKET AND HARD- WARE	
C100607	CE LABEL 12º	
C100506	CE LABEL-MEDIUM	
C100507	CE LABEL-SMALL	
C100508	CE LABEL-LARGE	

SOD CUTTER		
SOD COLLEK		



2 YEAR LIMITED SERVICE AND WARRANTY POLICY

Schiller Grounds Care, Inc.

1028 Street Road • Southampton, PA 18966

Telephone: 1-877-596-6337

TWO YEAR LIMITED WARRANTY

EffectiveJanuary 1, 2015

For the period of two years from the date of purchase, CLASSEN will repair or replace for the original purchaser free of charge, any part or parts found upon the examination of our factory authorized service station, or by the factory in Southampton, PA to be defective in material or workmanship. All transportation charges on parts submitted for repair or replacement under this warranty shall be borne by the purchaser.

This warranty does not include engines or engine parts, tires, batteries, or gearboxes that are covered under separate warranties furnished by their manufacturer or supplier, nor does it include normal maintenance parts, including but not limited to, spark plugs, points, filters, blades, and lubricants.

All service under this warranty will be furnished or performed by our factory authorized service stations.

There is no other expressed warranty. Implied warranties, including those of merchantability and fitness for a particular purpose, are limited to two years from the date of purchase and to the extent permitted by law, any and all implied warranties are excluded. The above remedy of repair and replacement of defective parts is the purchaser's exclusive remedy for any defect, malfunction or breach of warranty. Liability for incidental or consequential damages under any and all warranties is excluded to the extent permitted by law.

NORMAL RESPONSIBILITIES OF THE SELLER AND THE USER

- 1. The Distributor or Dealer is responsible for the proper assembly and preparation of the product for delivery to the end user.
- 2. The User is responsible for reading the Manual and Instructions.
- 3. The User is responsible for proper operation and maintenance as described in the manual.
- 4. The User is responsible for the replacement of wear items such as blades, belts, tires, batteries, etc.
- 5. The User is responsible for damage due to improper operation and maintenance, as well as abuse.

All claims must be received by the factory 30 days after the end of the warranty period to receive warranty consideration.

CLASSEN®
SCHILLER GROUNDS CARE, INC.
1028 STREET ROAD, P.O. BOX 38
SOUTHAMPTON, PA 18966
PHONE 877-596-6337 • FAX 215-357-8045